

New!



SIGNODE LB-2000™

Plastic strapping machine

**Jam-resistant
technology**

**Up to 52
straps per
minute**

**Maintenance-
free**

A worldwide leader in the development of superior strapping systems since 1913, Signode Packaging Systems introduces the LB-2000™ with the highest available speeds, most reliable performance and lowest maintenance operation of any general-duty strapping machine on the market today.



SIGNODE®

SIGNODE LB-2000™ Plastic strapping machine

A new generation of strapping systems from Signode

Jam-resistant technology

The LB-2000™ offers the most jam-resistant technology available in any plastic strapping machine today.

Unequaled speed

Cycling up to 52 straps per minute, the LB-2000 is the fastest standard machine in its class.

Automatic refeed

In the event of a non-completed feed, the machine automatically corrects itself.

Lubrication-free operation

The LB-2000's self-lubricating design provides excellent durability and maintenance-free operation.

Variable tension

Tension is easy to adjust using a single tension dial. Once the desired maximum tension level is set, you can change to low tension and back again with the simple flick of a switch.

Fully accessible strap path

Machine and strapping head covers are easily removed or fully opened, making the strapping head completely accessible.

Portable design

Four heavy-duty swivel casters (two locking), robust machine construction, compact design with space conserving dispenser and 110 volt electrical requirements simplify machine relocation and set up.

No adjustments

This is the only strapping machine available with no internal adjustments.

Strap size

Easy to change from 5mm to 6mm polypropylene strapping. No special parts are needed for the conversion.

Made in the U.S.A.

Options

Electric photo eye

Easily attached to the LB-2000, the photo eye triggers automatic strap cycling. A switch on the photo eye enables you to select one strap, continuous strapping or no straps.

Remote cycle switch

The portable cycle switch with heavy-duty magnetic backing can be positioned anywhere on or near the machine for the most convenient strap cycle activation.



SIGNODE®

3610 West Lake Avenue
Glenview, Illinois 60025
1-800-323-2464

Contrax® plastic strapping



Enhance the quality and performance of your LB-2000 strapping machine with Signode Contrax® polypropylene strapping.

- Consistent width and gauge control
- Smooth, uniform surface
- Resists splitting
- Recovers when elongated
- Available in various break strengths
- Recyclable (ask about Signode's recycling program)

LB-2000 Specifications

Production rate: Up to 52 straps per minute

Chute size: See illustration below

Minimum package size: 50mm x 25mm (2" x 1")

Strap tension: Adjustable up to 60 lbs.

Machine dimensions: 840mmW x 510mmL x 1400mmH (33"W x 20"L x 55"H), maximum height

Tabletop height: 865mm (34")

Electrical requirements: 110 volt, 60Hz

Shipping weight: 540 lbs.

Chute dimensions:

	Small chute		Large chute	
	mm	inches	mm	inches
A	600	23.75	730	28.75
B	420	16.75	420	16.75

